A1362

1-PL-A764
2-HT BOLT 1 X 4 3/4 (490)
2-HT WASHER 1 DIA (325)
(WRENCH TIGHT)

PLUG 1/16 WELD

HOLES (1"A490)

1-PL A763

MILL

ELEV. 465'-6 (FIN. 13TH FLOOR)

3'-6

5 1/2

22'-0

12'-9

ELEV. 452'-9 (FIN. 12TH FLOOR)

9'-3

12'-9

ELEV. 440'-0 (FIN. 11TH FLOOR)

3-6

A768 (NS)

1-1 1/4 1-1 1/4

BOTH FLGS

1-2 5/8 1-2 5/8

A767 (NS)

B767

A

B

+FB, 12, HT BOLT 1 X 4 1/4, 490, F., A
1-PL A752

FILLS

1-L AD (NS)

AA (FS)

HOLES (1DIA A490)

W 35 7/8 X 230 GIRDER A

W 35 7/8 X 230 GIRDER B

583=1'-3

583=1'-6

+FB, 7, HT BOLT 1 X 3, 490, F., A
1-PL A753 (OFFSET)

+FB, 6, HT BOLT 1 X 3, 490, F., A
1-PL C753 (OFFSET)

+FB, 12, HT BOLT 1 X3 3/4, 490, F., A
1-PL A752

1-1 1/8 1-1 1/8

G768 (NS)

1-1 7/16

1-1 3/8

1'-4 3/8

1'-4 7/16

18'-6 9/16

5'-9 9/16

1'-1 3/8

1'-1 7/16

5 5/8

5 3/8

3/8

1-L A768

1-PL A767

2-PL B767

1-L-AA

+FB, 2, HT BOLT 7/8 X 2 3/4, 325, F., A

AD

1-PL-PC

1-PL-PB

1-MC-G768

GRIND TO BEAR

W26 3/4X84

1'-9 7/8

22'-9 7/8

21'-6 1/2

3'-6 7/8

18'-5 1/8

23'-9 7/8

21'-6 7/8

19'-3 3/4

11'-0 7/8

10'-0 7/8

8'-9 1/2

6'-6 3/4

5'-8 1/8

X 7/8 SLOTS

1-8 1/4

GA=11 1/2

WEST

3 1/2

383=9

3 13/16

2 3/8

HOLES (1DIA.A490)

+FB, 16, HT BOLT 1 X 6 1/4, 490, F., A
+FB, 10, HT BOLT 1 X 4 3/4, 490, F., A

A1360

*DIV 1301, A1361, 1, W14X550, X 25-6 00, A36, M2E COL, P12, 19, (W 20 1/4 X 17 1/4 X 2 3/8 @ 550)

COL 26

"X 30" DIMS @ BASE

MATERIAL

: 8, PI 012 00 X00 3/4, X 1-9 1/2, A752, 44W, P1E, . . . A
: 2, PI 005 00 X00 1/2, X 1-6 1/2, C753, 44W, ... A
: 2, PI 017 7/8 X00 1/2, X 2-4 00, A767, 44W, BENT, . . . A
: 4, PI 006 1/2 X00 3/8, X 0-10 3/4, B767, 44W, ... A
: 2, PI 015 00 X00 5/8, X 2-1 1/2, A763, 44W, ... A
: 1, PI 010 00 X00 5/8, X 1-2 00, A764, 44W, ... n
: 2, PI 006 00 X00 3/4, X 1-3 00, PB, 44W, G1E, . . . A
: 2, PI 006 00 X00 3/4, X 1-0 1/2, PC, 44W, ... A
: 2, PI 005 00 X00 1/2, X 1-9 1/2, A753, 44W, ... A
2: 2, 9MCM25.4, X1-10 00, G768, A36, , P217, 2, , A
2: 2, L 6 X 4 X 5/16, X 2-6 00, A768, 44W, ... A
: 2, L 3 X 3 X 3/8, X 0-8 00, AD, 44W, ... A
: 2, HT BOLT 1 X 4 3/4, , , 490, ... A
: 2, HT WASHER 1 . . . 325, ... A

+FB, 148, HT WASHER 1, 325, , , A
: 1, 1F 3/16, X 12-0 00, , A
: 1, 1F 5/16, X 39-0 00, , A
: 1, 1F 3/8, X 6-0 00, , A
: 1, 1F 1/2, X 4-0 00, , A
: 1, 6G 5/8, X 8-0 00, , A

DRILLED HOLE

A763

NO WELD 4

1-2 1/2

1 1/8 X 15/16 SLOTS

AA

AD

A752

TYP

A767

B767

1" R

SECTION A-A

(7/8 DIA. A325) HOLES

PC (CUT TO FIT)

C753

A753

PB (FS)

SECTION B-B

SHOP NOTES
MATERIAL G40.21 44W U/N
E70 SERIES ELECTRODES
REF. D1AG'S E12, E13, 9102, 9103, E117, E118A, CW-1

DIM'S SHOWN IN BRACKETS ARE BASED ON ACCURATE COL SIZES.

SHOP SCRIBE VISIBLE C/L ON BOTH FLGS & B/S WEB TOP & BOTT.

June 2/85R
May 29/85R
May 1/85

FOR 1 DIA A490

R 3	DATE	BY	SPEC	AS NOTED	FRANKEL STEEL LIMITED
E 2	DATE 06 JUN 85	BY MK	HOLES	1 3/16 D1A U/N	220 ATTWELL DRIVE, UNIT 1, REXDALE, ONTARIO M9W 5Z2
V 1	DATE 29 MAY 85	BY JIM	FINISH	NONE	
MADE 27 MIKIM	DATE 08MAY85	SQUAD FR	PROJECT: 7 WORLD TRADE CENTER		CONTRACT 84-152
CHK'D 28 JIM	DATE 13MAY85		DETAIL: COLUMN (7TH TIER) (ZONE 2)		DWG. NO. 1361